

Aspöck LumEU Flex High Protection Professional 850lm/White-24V-90- 2200K/2700K/3000K/3500K/4000K/5000K/6000K/6500K

Flexible LED-strip with IP66 protection due to PUR surface encapsulation

PRODUCT FEATURES

- Length 5000 mm open end
- Resistant to dust, water jets, UV radiation, abrasion and chemicals
- Estimated lifetime L80 at $T_a < 45^\circ\text{C} >$ 60.000 hours
- Connection via 0,2m cable with open ends
- With high-quality 3M double adhesive tape



PHOTOMETRIC DATA

ARTICLE.NO.	30-2200-227	30-2200-027	30-2200-257
Color Temperature [K]	2200	2700	3000
Luminous Flux per Meter lm/m (Effective)	671	695	720
Efficiency [lm/W]	69	72	75
Luminous Flux per Meter (Center Point 4000K)	850		
CRI	>90		
LED per meter	120		
Beam Angle	120 °		
Estimated Lifetime L80 at $T_a < 45^\circ\text{C}$	60.000 hours		

PHOTOMETRIC DATA

ARTICLE.NO.	30-2200-037	30-2200-047	30-2200-057
Color Temperature [K]	3500	4000	5000
Luminous Flux per Meter lm/m (Effective)	818	861	928
Efficiency [lm/W]	85	89	96
MacAdam	X	3	3
Luminous Flux per Meter (Center Point 4000K)	850		
CRI	>90		
Beam Angle	120 °		
Estimated Lifetime L80 at Ta < 45°C	60.000 hours		

PHOTOMETRIC DATA

ARTICLE.NO.	30-2200-067	30-2200-077
Color Temperature [K]	6000	6500
Luminous Flux per Meter lm/m (Effective)	875	919
Efficiency [lm/W]	91	95
MacAdam	3	
Luminous Flux per Meter (Center Point 4000K)	850	
CRI	>90	
Beam Angle	120 °	
Estimated Lifetime L80 at Ta < 45°C	60.000 hours	

ELECTRICAL DATA

Technology	IC
Voltage	24 V DC
Electrostatic Discharge	800 V
Power per Meter	9.6 W/m
Operating Temperature	-20~+50 °C
Storage Temperature	-40~+80 °C
Protection	IP 66

MECHANICAL DATA

Length	5000 mm
Width	8 mm
Height	3 mm
Min. Bend Radius	5 cm
Max. Length*	15 m

*The value given applies to the application of the rated voltage at the first module section. When using a supply line, the maximum operable length changes depending on the supply line length and its cross section.

The stated photometric data are typical values, which are influenced by the binning of the LEDs and the encapsulation process. Each of these factors affect the tolerances, therefore the resulting photometric data can deviate from the stated typical values.

All listed data can have a tolerance value of +/- 15%. Typing and printing errors reserved.